

GRABFAST

THE ROOFING SOLUTION



Features

- Portable system
- Ease of application
- Self contained and maintenance free
- Excellent bond strength
- Ready to bond within minutes
- Waterproof
- Non flammable

Technical Data

Chemical Name	Sprayable contact adhesive
Appearance	Liquid
Coverage	15 sqm per Kg
Glue	38-42%
Shelf Life	1 Year
Temperature Stability	120°C

GRABFAST The Roofing Solution has been specifically designed to bond EPDM Rubber and Insulation to a wide spectrum of substrates. It offers the user a fast, reliable and portable alternative to traditional methods whilst leaving an excellent bond that is both waterproof and non-flammable. The bulk aerosol system reduces costs by saving application time with no wastage at all.

Application

All surfaces to be bonded should be dry, clean, grease and dust free. Hold the spray gun parallel to the substrate and apply an even coat of adhesive across it, a webbing effect should be created. Do not allow the adhesive to puddle or concentrate in one area. In order to prevent this from happening the spray gun is fully adjustable by turning the wheel located behind the trigger. The wider the spray pattern being applied the further away the nozzle should be held. The tip of the spray gun should always be kept clean. It is recommended that you keep a spare tip, one in use and one cleaning, additional tips are available from your local representative.

It is important to remember that **GRABFAST** is a contact adhesive and forms its bond by sticking to itself hence there must be sufficient adhesive on both substrates to allow this to happen. On Insulation the coverage should be approximately 80%. It should be noted that it can be applied directly onto the insulation. On EPDM rubber the user should ensure that 100% coverage is achieved.

The two surfaces are ready to bond when the adhesive is dry to the touch with no transference to the fingers; once they are brought together a roller should be used to achieve maximum performance. It is the users responsibility to ensure the suitability of **GRABFAST** for the substrates that are to be bonded. If you are unsure please do not hesitate to contact our technical service department for advice.



This container will be collected for recycling
FREEPHONE
0800 3284267
INTERNATIONAL STANDARD
ISO 14021
TYPE II ENVIRONMENTAL CLAIM

gemini

...creating lifetime bonds

ADHESIVES | R & D | EXTRUSIONS | SUSTAINABILITY

Gemini Adhesives Limited, New Building, Top Road, Osgathorpe, Leicestershire, LE12 9TB.
Freephone Sales Line UK: 0800 3284267 **Email: info@geminiadhesivesgroup.com**

www.geminiadhesivesgroup.com